

# WORLD DGNSS

## C-Nav 1000



### C-Nav 1000 FEATURES:

- Fully compliant with IMO and IEC specifications for shipboard GPS. (Wheelmark and US Coast Guard compliant).
- The Navigation control and display panel has red, yellow and green “traffic lights” in accordance with IEC RAIM specifications. This visual indication allows for the user to monitor the integrity of the GPS solution in real time.
- Can connect to existing or future SAAB AIS systems to ensure that the vessel operates in full compliance with all relevant regulations.
- Display and control navigation data and AIS information when combined with the SAAB AIS configuration.

## FEATURES

### GENERAL

- Waypoints: 2,000 waypoint memory
- Routes: 100 routes, using a total of 2,000 waypoints
- Functions: Navigation, Position, Route, Waypoint, Event mark, Plot, Sail To, MOB, GPS/DGPS, Alarms, Speed, Graph, Configuration, Trip Log, Anchor Watch, Scheduled Alerts
- Integrity: The product performs RAIM calculations in accordance with IEC 61108-1 Ed.2
- Supply: 10.5 - 30V DC, 12.5W
- Display: High resolution 6 inch, 1/4 VGA monochrome, sunlight readable
- LEDs: 1 power and 3 RAIM status (R/Y/G)
- Mounting: Yoke or flush mounting of display unit

## PHYSICAL/ENVIRONMENTAL

### DIMENSIONS (W x H x D)

- Control and Display Unit: 10" x 8" x 4" (270 x 207 x 102 mm)
- Navigation Sensor: 5" x 1" x 5" (128 x 39 x 137 mm)

### WEIGHT

- Control and Display Unit: 2.4 lbs (1.1 kg)
- Navigation Sensor: 1 lbs (0.5 kg)

### ENVIRONMENTAL

- Control and Display Unit Operating Temperature: -15° C to +55° C
- Navigation Sensor Operating Temperature: -30° C to +70° C
- Protected Environment: (IEC 60945)

### CABLES

- Power/Data Cable to Navigation Sensor: 7' (2m), 18 pin MaxiCon-pigtail
- Data Cable to Control and Display Unit: 7' (2m), 18 pin MaxiCon-pigtail
- Power cable to Control and Display Unit: 7' (2m), 3 pin MaxiCon-pigtail
- GPS Antenna Cable (recommended): LMR400; Max length 150' (45m); TNC connector

\* IMO require all SOLAS class ships to carry a type-approved GPS and further that any new GPS installation shall be compliant with the new performance standard for GPS. This was defined by MSC 112(73) and resulted in the associated test standard IEC 61108-1 Ed. 2.

\*\* Dependent upon ionospheric activity and multipath

\*\*\* SVs > 5, HDOP < 2, RTCM SC-104 correction data from a dual frequency reference station, short baseline and low multipath environment.

## PERFORMANCE

### GPS RECEIVER

- 12 channel L1, C/A-code with carrier phase smoothing (10 channels, when tracking WAAS, EGNOS and MSAS)
- Update rate: 1 Hz default, 5 Hz max
- Position accuracy: GPS\*\*: 5m, DGPS\*\*\*: 1m
- Cold start time: 1 minutes typical

### DGPS BEACON RECEIVER

- Dual receiver: manual or automatic tuning
- Frequency: 283.5 to 325.0 kHz
- MSK Bit Rates: 50, 100 and 200 bps
- Cold Start Time: < 1 minute typical
- Reacquisition: < 2 minute typical
- Sensitivity: 2.5µV/m for 6db SNR@ 200 bps

### INTERFACE

- 2 bi-directional user ports RS422
- 1 output port RS422
- Ports are configurable 4,800 - 38,400 bps
- 1 alarm output for relay activation
- 1 input
- Log pulse output

## I/O CONNECTOR ASSIGNMENTS

### INPUT/OUTPUT DATA MESSAGES

- NMEA Messages: APB, BOD, BWC, BWR, DBT, DPT, DTM, GBS, GGA, GLL, GNS, GSV, HDG, HDT, HSC, RMB, RMC, RTE, VHW, BTG, WPL, XTE, ZDA
- Proprietary messages: For RAIM control and display
- RTCM SC-104: Type 1, 2, 9

## COMPLIANCE/APPROVALS

- Compliance with the following standards:
  - > IMO performance standard for GPS\* > IEC 61108-1 Ed2, GPS
  - > IEC 61162-1/2 Ed2, NMEA 0183, versions 2.0 through 3.0
- Type Approvals:
  - > Wheelmark
  - > USCG



WWW.CNAVGNSS.COM

Specifications subject to change without n  
© 2011 C & C Technologies, Inc.

**LAFAYETTE (HEADQUARTERS)**  
730 E. KALISTE SALOOM RD.  
LAFAYETTE, LOUISIANA 70508  
TEL: (+1) 337.210.0000  
FAX: (+1) 337.210.0003

**HOUSTON**  
10615 SHADOW WOOD DR  
SUITE 100  
HOUSTON, TEXAS 77043  
TEL: (+1) 713.468.1536  
FAX: (+1) 713.468.1115

**MEXICO**  
CALLE 55 N° 382  
COL OBRERA INTER 74 y 76  
CIUDAD DEL CARMEN, CAMPECHE  
CP 24117, MEXICO  
TEL: (+52) 938.381.8973  
FAX: (+52) 938.381.8973

**BRASIL**  
AV. DAS AMERICAS, 11889 - 3° ANDAR - BARRA DA TIJUCA  
Cep: 22793-082 - RIO DE JANEIRO - RJ  
RIO DE JANEIRO, BRASIL  
TEL: 55.21.2499.9500  
FAX: 55.21.2498.5042

**EUROPE**  
5 HILLSIDE BUSINESS PARK (1ST FLOOR)  
KEMPSON WAY  
BURY ST EDMUNDS  
SUFFOLK, IP32 7EA, UK  
TEL: (+44) 1284.703.800  
FAX: (+44) 1284.701.004

**SINGAPORE**  
10 CHANGI SOUTH LANE  
OSSIA INTERNATIONAL BUILDING #03-01B  
SINGAPORE 486162  
TEL: (+65) 6295.9738  
FAX: (+65) 6296.0098

**SOUTH AFRICA**  
C & C HOUSE @ SHIP ASHORE  
53 PENINSULA ROAD  
ZEEKOEVLEI, CAPE TOWN 7941  
SOUTH AFRICA  
TEL: (+27) 21.705.2741  
FAX: (+27) 21.705.2741

**ANGOLA**  
RUA ANTONIO MARQUES  
MONTEIRO N° 36/38  
LUANDA - ANGOLA  
TEL: (+244) 222.330202  
FAX: (+244) 222.335464